# E-Series High-end Rental Display

SAFEEYE

## Application

1. Curved lock option to support concave and convex freely

2. 500x500mm/500x1000mm cabinets can be mixed and spliced freely to meet the needs of different application scenarios

## Technical Parameter

| | |
|---|---|
| Item | SA-DLE60 |
| Module Size (W×H×D)mm | 250*250*16 |
| Module Resolution (W×H) | 96*96 |
| Scanning Mode | 1/32 |
| LED Configuration | 1R1G1B |
| LED Type | SMD1515 |
| Maintenance Method | Front or back service |
| Installation Method | back installation |
| Cabinet Size (W ×H ×D) mm | 500*500*90 |
| Cabinet Resolution (W ×H) | 192*192 |
| Physical Density (dot/m²) | 147456 |
| Brightness | 700~900 |
| Max. Power Consumption | 650W |
| Average Power Consumption | 200W |
| Weight | 7.3KG |
| Cabinet Material | Die Casting Aluminum |
| Protection Level | IP54 |
| Contrast Ratio | ≥5000:1 |
| Grey Scale (Bit) | 14bit |
| Refresh Rate） | 3840Hz |
| Refresh Frame Frequency | 50/60Hz |
| Horizontal View Angle | ≥140° |

## Features

- Pitch: E2.60/E2.97/E3.91/EH3.91/EH4.81
- Cabinet customized curved designs and 90° splicing
- Pluggable power box
- TUV-certified multifunctional hanging bars and four anti-collision corners perfect protect lamps.

| | |
|---|---|
| Vertical View Angle | ≥120° |
| Optimal Viewing Distance | 3M |
| Power Input Voltage | AC110V~AC220V |
| Module Max Current | 8.5A |
| Working Temperature | -20℃~+80℃ |
| Working Humidity | 10%RH~95%RH |
| Life Time | ≥100000 |
| MTBF | ≥10000 |

| Item | SA-DLE61 |
|---|---|
| Module Size (W×H×D)mm | 250*250*15.5 |
| Module Resolution (W×H) | 84*84 |
| Scanning Mode | 1/28 |
| LED Configuration | 1R1G1B |
| LED Type | SMD1515 |
| Maintenance Method | Front or back service |
| Installation Method | back installation |
| Cabinet Size (W ×H ×D) mm | 500*500*90 |
| Cabinet Resolution (W ×H) | 168*168 |
| Physical Density (dot/m²) | 112896 |
| Brightness | 700~900 |
| Max. Power Consumption | 650W |
| Average Power Consumption | 200W |
| Weight | 7.3KG |
| Cabinet Material | Die Casting Aluminum |
| Protection Level | IP54 |
| Contrast Ratio | ≥5000:1 |
| Grey Scale (Bit) | 14bit |
| Refresh Rate） | 3840Hz |
| Refresh Frame Frequency | 50/60Hz |
| Horizontal View Angle | ≥140° |
| Vertical View Angle | ≥120° |
| Optimal Viewing Distance | 3M |
| Power Input Voltage | AC110V~AC220V |
| Module Max Current | 8.5A |
| Working Temperature | -20℃~+80℃ |
| Working Humidity | 10%RH~95%RH |
| Life Time | ≥100000 |
| MTBF | ≥10000 |

| Item | SA-DLE62 |
|---|---|
| Module Size (W×H×D)mm | 250*250*15.5 |
| Module Resolution (W×H) | 64*64 |
| Scanning Mode | 1/16 |
| LED Configuration | 1R1G1B |
| LED Type | SMD2121 |
| Maintenance Method | Front or back service |
| Installation Method | back installation |
| Cabinet Size (W ×H ×D) mm | 500*500/1000*90 |
| Cabinet Resolution (W ×H) | 128*128/128*256 |
| Physical Density (dot/m²) | 65536 |
| Brightness | 700~1000 |
| Max. Power Consumption | 650W |
| Average Power Consumption | 200W |
| Weight | 7.3KG/11KG |
| Cabinet Material | Die Casting Aluminum |
| Protection Level | IP54 |
| Contrast Ratio | ≥5000:1 |
| Grey Scale (Bit) | 14bit |
| Refresh Rate） | 3840Hz |
| Refresh Frame Frequency | 50/60Hz |
| Horizontal View Angle | ≥140° |
| Vertical View Angle | ≥120° |
| Optimal Viewing Distance | 4M |
| Power Input Voltage | AC110V~AC220V |
| Module Max Current | 8.5A |
| Working Temperature | -20℃~+80℃ |
| Working Humidity | 10%RH~95%RH |
| Life Time | ≥100000 |
| MTBF | ≥10000 |

| Item | SA-DLE63 |
|---|---|
| Module Size (W×H×D)mm | 250*250*16.5 |
| Module Resolution (W×H) | 64*64 |
| Scanning Mode | 1/16 |
| LED Configuration | 1R1G1B |
| LED Type | SMD1921 |
| Maintenance Method | back service |
| Installation Method | back installation |
| Cabinet Size (W ×H ×D) mm | 500*500/1000*90 |
| Cabinet Resolution (W ×H) | 128*128/128*256 |
| Physical Density (dot/m²) | 65536 |
| Brightness | 3300/5500 |
| Max. Power Consumption | 800W |
| Average Power Consumption | 260W |
| Weight | 7.3KG/11KG |
| Cabinet Material | Die Casting Aluminum |
| Protection Level | IP65 |
| Contrast Ratio | ≥5000:1 |
| Grey Scale (Bit) | 14bit |
| Refresh Rate） | 3840Hz |
| Refresh Frame Frequency | 50/60Hz |
| Horizontal View Angle | ≥140° |
| Vertical View Angle | ≥120° |
| Optimal Viewing Distance | 4M |
| Power Input Voltage | AC110V~AC220V |
| Module Max Current | 12A |
| Working Temperature | -20℃~+80℃ |
| Working Humidity | 10%RH~95%RH |
| Life Time | ≥100000 |
| MTBF | ≥10000 |

| Item | SA-DLE64 |
|---|---|
| Module Size (W×H×D)mm | 250*250*16.5 |
| Module Resolution (W×H) | 52*52 |
| Scanning Mode | 1/13 |
| LED Configuration | 1R1G1B |
| LED Type | SMD1921 |
| Maintenance Method | back service |
| Installation Method | back installation |
| Cabinet Size (W ×H ×D) mm | 500*500/1000*90 |
| Cabinet Resolution (W ×H) | 104*104/104*208 |
| Physical Density (dot/m²) | 43264 |
| Brightness | 3300/5500 |
| Max. Power Consumption | 800W |
| Average Power Consumption | 260W |
| Weight | 7.3KG/11KG |
| Cabinet Material | Die Casting Aluminum |
| Protection Level | IP65 |
| Contrast Ratio | ≥5000:1 |
| Grey Scale (Bit) | 14bit |
| Refresh Rate） | 3840Hz |
| Refresh Frame Frequency | 50/60Hz |
| Horizontal View Angle | ≥140° |
| Vertical View Angle | ≥120° |
| Optimal Viewing Distance | 5M |
| Power Input Voltage | AC110V~AC220V |
| Module Max Current | 12A |
| Working Temperature | -20℃~+80℃ |
| Working Humidity | 10%RH~95%RH |
| Life Time | ≥100000 |
| MTBF | ≥10000 |