



Advantage:

- 3 in 1 access controller with 3 options:
- 1, 1 door 2 reader
- 2, 2 door 2 reader
- 3, Turnstile gate access controller

Technical Parameter

Model.NO	SA-CAS-1.3
Management door number	single door two-way double door two-way four one-way door
Open the door way	swipe card, password
Storage registration cards	20,000
Communication mode	TCP/IP
Stored records	100,000
Real-time monitoring	Supported
Product size	146*85*30mm
Circuit board function	less than 100mA
Support database	Access or SQL
Offline	Supported
Main board hole position	129*69mm
Card reader input format	Wiegand 26 or 34 bit
Door delay time	1-600 seconds adjustable
Data off network protection	fast storage speed, no data loss
Ambient humidity	10-90% RH, no condensation
Card reader to the controller online distance	100 meters, 80 meters recommended On-line distance
distance between electric lock and controller	50 meters (1.0) is recommended, and the power cord should be thickened if exceeded

About this item

Distance between controller and switch: within 100 meters, exceeding the use of switch Web management feature: not supported

Mobile phone access control function: not supported

Data off network protection: fast storage speed, no data loss

Function description: you can swipe the card and go out button for 1/2/4 doors, or swipe the card in and out of doors (for 4 doors)

Network Interface Equipped with network interface, connect network switch interface element component interface, signal transmission fast, connect network data accurately. The hardware uses B/S, C/B two kinds of structure, the user can use IE or management software to manage

Controller terminal the use of screw screw connection, firm and durable. Reserved controller fixed mounting hole, convenient to be fixed in the power box

Magnet adsorption Equipped with magnet, no screw fixed, automatic adsorption is simple and convenient

Product components The internal components of the product are all original components, which are stable and durable in operation. In the use of relevant functions, the relevant indicator light will light up, played a reminder to inform the effect, safe and correct operation..